






CLF10040T-680M-CA

Applications		Automotive Grade
Feature		Wire Wound
		Magnetic Shield
		Ferrite Core
		AEC-Q200
Series	CLF-CA Series / CLF10040-CA Type	
Status	Production	



Size	
Length(L)	10.00mm +/-0.30mm
Width(W)	9.70mm +/-0.30mm
Thickness(T)	3.80mm +/-0.30mm
Recommended Land Pattern (A)	2.50mm Nom.
Recommended Land Pattern (B)	5.60mm Nom.
Recommended Land Pattern (C)	3.20mm Nom.


Electrical Characteristics	
Inductance	68uH +/-20% at 100kHz
Rated Current (L Change) [Typ.]	1.6A (10% Down)
Rated Current (Temperature Rise) [Typ.]	1.1A (30degC Rise)
DC Resistance [Nom.]	180mΩ
DC Resistance [Max.]	216mΩ

Other	
Operating Temp. Range (Including Self-Temp. Rise)	-40 to 105degC
Soldering Method	Reflow, Iron Soldering
AEC Q200	Yes
Packing	Blister (Plastic)Taping [330mm Reel]
Package Quantity	800Pcs Min.
Weight	1.3g


•This PDF document was created based on the data listed on the TDK Corporation website.
 •All specifications are subject to change without notice.

CLF10040T-680M-CA


Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)




CLF10040T-680M-CA



CLF10040T-680M-CA



CLF10040T-680M-CA




CLF10040T-680M-CA


•This PDF document was created based on the data listed on the TDK Corporation website.
 •All specifications are subject to change without notice.

CLF10040T-680M-CA

Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)




CLF10040T-680M-CA(Amb. Temp. = 20degc)



CLF10040T-680M-CA(DC = 0A)

CLF10040T-680M-CA(DC = 0.55A)



CLF10040T-680M-CA(Amb. Temp. = 20degc)

- This PDF document was created based on the data listed on the TDK Corporation website.
- All specifications are subject to change without notice.